Business Desktop

19" | 22" | 23" | 24" | 27" | 29"

NEC MultiSync® EA Series

High-performance, LED-backlit LCD displays ideal for corporate environments

Reimagine your desktop computing experience. With its next generation MultiSync EA Series, NEC has developed monitor solutions that push the boundaries of what you've come to know as business-grade screen performance. The 19" MultiSync EA193Mi, 22" EA224WMi and EA223WM, 23" EA234WMi, 24" EA243WM and EA244WMi, 27" EA273WMi and 29" EA294WMi deliver a completely redesigned chassis with a host of enhanced features, advanced technologies, future-proof connectivity and environmentally friendly benefits. Select models tout an IPS module, which boasts the best possible color accuracy and minimal viewing angle shift.

These models boast LED backlight technology, which not only reduces power by up to 52% compared to their predecessors, but leads to a 30% thinner and 25% lighter chassis. Other green features include ECO Mode™, a carbon footprint meter and an ambient light sensor, which automatically adjusts the brightness to the optimal setting depending on ambient lighting, screen content or both, conserving power up to 87% compared to typical energy consumption. In addition, the human sensor detects user activity in front of the monitor and reduces display power up to 95% with inactivity.

The ground breaking ControlSync™ feature allows users to control up to six next-generation MultiSync EA Series units in a multi-monitor configuration. Upon establishing one unit as the master, you will be able to simultaneously control many performance attributes of the multi-monitor setup through the master monitor.

Highlights

- **LED backlight technology** provides for industry-leading low power consumption and less hazardous materials
- **Four-way ergonomic stand** boasts pivot, tilt, swivel and height adjustment up to 130mm to maximize your viewing comfort
- **Touch-sensitive OSD® controls** are integrated into the bezel, making display adjustments easier than ever
- **Integrated 4-port USB 2.0 hub** easily connects you to your peripherals
- **Comprehensive input panel**, including DisplayPort, HDMI, DVI-D and 15-pin VGA, connects you to the latest peripherals and future-proofs your investment
- **Space saving, multimedia speakers**, which enhance your computing experience, are hidden to maintain the monitor's aesthetic appeal (headphone jack also included)
- **ControlSync** enables multi-monitor setups of up to six monitors and controls up to 26 settings
- **Customize Setting** allows both users and IT administrators to set and restore preferred settings with just one touch, contributing to a free-seating business environment
- **Smart sensing technology** includes ambient light and human sensors, which considerably reduce power consumption by automatically detecting your work conditions and adjusting to the proper display brightness or entering Power Saving Mode
- **Carbon footprint meter** helps track and calculate the reduction of green gas emissions, while the resettable cost meter (via On Screen Display) indicates electricity cost savings based on currency settings
- **NaViSet™ software** offers an intuitive graphical interface, allowing for easy adjustment of display settings via mouse and keyboard. NaViSet Administrator provides all the advanced control to remotely located IT professionals.
- **EPEAT Silver/Gold compliance** ensures the displays reduce hazardous waste and electricity usage, resulting in lower energy costs and increased protection for the environment
- **ENERGY STAR® compliance** reduces electrical costs and lowers total cost of ownership

Specifications for MultiSync EA193Mi/EA224WMi/EA223WM/EA234WMi/EA243WM/EA244WMi/EA273WMi/EA294WMi

MODEL	EA193Mi	EA224WMi	EA223WM	EA234WMi	EA243WM	EA244WMi	EA273WMi	EA294WMi
DISPLAY								
Panel Technology	IPS		TN	IPS	TN	IPS	AH-IPS	IPS
Backlight Type	W-LED							
Viewable Image Size	19"	21.5"	22"	23"	24"		27"	29"
Aspect Ratio	5:4	16:9	16:10	16:9	16:10		16:9	21:9
Native Resolution	1280 x 1024	1920 x 1080	1680 x 1050	1920 x 1080	1920 x 1200		1920 x 1080	2560 x 1080
Pixel Pitch	0.29mm	0.248mm	0.282mm	0.267m	0.27mm		0.311mm	0.262mm
Pixels Per Inch	86 @ native resolution	102 @ native resolution	90 @ native resolution	96 @ native resolution	94 @ native resolution		82 @ native resolution	97 @ native resolution
Brightness (typical)	250 cd/m²					350 cd/m²	300 cd/m²	
Contrast Ratio (typical)	1000:1 (25,000: dynamic)							
Viewing Angle (typical)	178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10		160° Vert., 170° Hor. (80U/80D/5L/85R) @ CR>10	178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10	160° Vert., 170° Hor. (80U/80D/85L/85R) @ CR>10	178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10	178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10	
Response Time (typical)	6ms	6ms (with overdrive)	5ms	6ms	5ms		6ms	
Displayable Colors	More than 16.7 million							
Synchronization Range								
Horizontal (Analog/Digital)	31.5-81.1 kHz	31.5-83 kHz	31.5-82.3 kHz	31.5-83 kHz	31.5-77 kHz		31.5-83 kHz	
Vertical	56-75 Hz				56-60 Hz		56-75 Hz	
Input Signal								
Video	Analog RGB 0.7 Vp-p/75 Ohms							
Sync	Separate Sync: TTL Level (Positive/Negative); Composite Sync: TTL Level (Positive/Negative); Composite Sync on Green: (0.3Vp-p negative 0.7Vp-p positive)							
Input Connectors	DisplayPort, DVI-D, VGA 15-pin D-sub	DisplayPort, HDMI, DVI-D, VGA 15-pin D-sub	DisplayPort, DVI-D, VGA 15-pin D-sub	DisplayPort, HDMI, DVI-D, VGA 15-pin D-sub				VGA 15-pin D-Sub (2), DVI-D (2), DisplayPort, HDMI / MHL
POWER CONSUMPTION								
On (typical)	18W	26W	25W	27W	29W		31W	50W
Power Savings Mode (typical)	0.35W	0.43W	0.4W	0.41W	0.48W	0.47W	0.48W	0.8W
PHYSICAL SPECIFICATIONS								
Dimensions (WxHxD)								
Net (with stand)	16.1 x 15.2-19.5 x 8.4 in. / 408 x 386.4-496.4 x 213.9mm	20 x 14.6-19.7 x 8.6 in. / 507.4 x 370.2-500.2 x 218mm	19.8 x 15.1-20.2 x 8.6 in. / 503.5 x 384-514 x 218mm	21.4 x 15.0-20.1 x 8.7 in. / 543.8 x 380.4-510.4 x 218mm	21.9 x 16.1-21.2 x 9.1 in. / 556.2 x 408.9-538.9 x 230mm		25.2 x 16.5-21.6 x 9.1in / 639.3 x 418-548 x 230mm	27.8 x 16.2-21.3 x 9.1 in. / 705.8 x 410.4- 540.4 x 230mm
Net (without stand)	16.1 x 13.3 x 2.6 in. / 408 x 338 x 65mm	20 x 11.9 x 2.4 in. / 507.4 x 301.1 x 60.5mm	19.8 x 13 x 2.4 in. / 503.5 x 329.7 x 60.5mm	21.4 x 12.7 x 2.4 in. / 543.8 x 321.6 x 60.5mm	21.9 x 14.2 x 2.5 in. / 556.2 x 359.6 x 63.8mm		25.2 x 14.9 x 2.6 in. / 639.3 x 377.8 x 66.5mm	27.8 x 12.7 x 2.7 in. / 705.8 x 321.8 x 69.1mm
Weight								
Net (with stand)	13.2 lbs. / 6.0 kg	13.2 lbs. / 6 kg	12.3 lbs. / 5.6 kg	14.1 lbs. / 6.4 kg	15.4 lbs. / 7 kg	16.8 lbs. / 7 kg	15.9 lbs. / 7.2 kg	21.2 lbs. / 9.6 kg
Net (without stand)	8.8 lbs. / 4.0 kg	8.2 lbs. / 3.7 kg	7.3 lbs. /3.3 kg	8.8 lbs. / 4.0 kg	9 lbs. / 4.1 kg	10.6 lbs. / 4.8 kg	9.5 lbs. / 4.3 kg	14.6Lbs. / 6.6 kg
VESA Hole Configuration	100 x 100mm							
ENVIRONMENTAL CONDITIONS								
Operating Temperature	41-95°F / 5-35°C							
Operating Humidity	20 - 80%							
Operating Altitude	6562 ft. / 2000m							10,000 ft. / 3048m
Storage Temperature	14-140°F / -10-60°C							
Storage Humidity	10-85%							
Storage Altitude	40,000 ft. / 12,192m							
Tropical Environments	Yes							
ENVIRONMENTAL COMPLIANCE								
ENERGY STAR	6.0							
TCO	6.0	5.2		Edge 1.2	5.2	6.0		5.0
EPEAT	Silver	Gold	Silver	Gold				
RoHS	Yes							
LIMITED WARRANTY	3 years parts and labor, including backlight*							
ADDITIONAL FEATURES	Tilt; Swivel; Pivot; Height-adjustable stand; ControlSync; Customize Setting; Integrated speakers; 4-port USB hub; LED backlit; Auto brightness with ambient light sensor; Human sensor; ECO Mode; Carbon footprint meter; Resettable cost meter; Thin frame; Carrying handle; Rapid Response; Ambix; XtraView; Hot Key; Touch OSD controls; OSD Lock Out; Cable management; Dynamic Visual Mode (Standard, Text, Movie, Gaming, Photo, Dynamic); NaViSet software; VESA mount; HDCP; DDC/CI; No Touch Auto Adjust; Plug and Play (VESA DDC2B); VESA DPMS power management; AccuColor color control; Digital smoothing; Digital controls; ISO 9241-307 Class I; DICOM SIM for IPS models							
SHIPS WITH	Setup sheet; User manual; Power cord; 15-pin D-sub cable; DVI-D cable; USB cable; Audio cable; ControlSync cable							

* Warranty restrictions apply. Contact your representative for details.

Touch-sensitive OSD controls



Comprehensive input panel (select models)

USB 2.0 hub

4-way adjustable stand

Thin, lightweight design with integrated speakers

Ambient and human sensors

ENERGY STAR

MultiSync is a registered trademarks and ECO Mode and ControlSync are trademarks of NEC Display Solutions. All other brand or product names are trademarks or registered trademarks of their respective holders. Product specifications subject to change.

©2013 NEC Display Solutions of America, Inc. All rights reserved.

25.NEC.80.GL.UN.029 rev 9.23.13

NEC Display Solutions
500 Park Boulevard, Suite 1100
Itasca, IL 60143
866-NEC-MORE

necdisplay.com